



Displayed model  
4 pairs of ski boots + 4 pairs of gloves

## K-STOCKDRY-A WALL-MOUNTED BOOT-DRYER

The REFERENCE in wall-mounted boot-dryer.

The K-STOCKDRY-A condenses a maximum of technologie in a minimum of space :  
Timer, electronic controls, a fully modular system (boots, gloves, helmets), space-saving design and outstanding ruggedness.

Wide range of sizes and finishes.

### Main features :

#### Optimized Space

The different models offer the possibility to choose the most adapted one to your area, in a reduced space.

#### Anti-corrosion Treatment

EPOXY painting finish.

Body RAL 7004 - Ventilation unit RAL 7024.

#### Heated Air Ventilation System

The heated air ventilation system, via the tubes with clap, allows to quickly dry elements (boots, gloves, helmets...).

#### Small Space Requirement

The K-STOCKDRY-A has a slim design (4 cm), which means optimises the use of space on the premises. The ventilation unit is located on the top of K-STOCKDRY-A for an extra pair of boot.

### OPTIONS



K-GLOVE-2  
For 1 pair of gloves or 1 helmet.  
To be screwed in place of a boot support.



K-GLOVE-1  
For 1 glove.  
Tongue to screw into the back of a boot support

**TIMER VERSION :**

Timer function : 2h, 3h or unlimited hours with an automatic shut-off.

Factory setting of 2 hours can be changed.

**PROGRAMMABLE VERSION :**

Integrated programming clock.

Up to 4 time slot per day.

For each time slot, you can schedule a duration and the type of drying (ventilation with or without heating).

**WELL THOUGHT-OUT DESIGN FOR AN EASIER USE AND MAINTENANCE**

Unit on top of the device to secure the electrical system (dust and moisture) and optimize the drying space (an extra pair of boots).

The unit works separately from the rest of the body

Integrated wall-mounting system.



**Modularity :** possibility to change the tubes with clap by gloves or helmet holder.



Examples of existing configurations

**Delivered in a kit (2 boxes)  
Simply assembly - Screws supplied.**

Main references TIMER	↓	↔	↗	Capacity
K-SD-04SP-AT-02.00.00	1430	180		2 Pairs
K-SD-06LP-AT-03.00.00	2080			3 Pairs
K-SD-08SP-AT-04.00.00	1430		330	4 Pairs
K-SD-10MP-AT-05.00.00	1750	270		5 Pairs
K-SD-12LP-AT-06.00.00	2080			6 Pairs
<b>Consumption</b>	550 W			

Dimensions without boots in mm.  
Capacity : BOOTS (in Nb of pairs)

**FEATURES OF THE UNIT**

Powerfull turbine (280 m<sup>3</sup>/h).

Accessible fuse holder (with backup fuse).

Electrical sensor to regulate the heating temperature.

**Recommandations**

220V power - IEC plug on top of the unit.  
Available in 100-110 V power

Operates on a standard plug / Plan to put a plug above the boot-dryer.

Consumption : 530 W/H.