

## K-STOKDRY-A

Wall-mounted boot dryer



The reference in wall-mounted boot drying. The K-STOKDRY condenses a maximum of technology in a minimum of space: timer, electronic controls, a fully modular system (boots, gloves, helmets), space-saving design, and outstanding ruggedness.

### GENERAL FEATURES

#### + Optimized space

The different models offer the possibility to choose the most adapted one to your area, in a reduced space.

#### + Heated air ventilation system

Its heated air ventilation system, via the tubes with clap allows to quickly dry the elements (shoes, gloves, helmets...).

#### + Timer

**STANDARD VERSION** : Timer function (2H).

+ **VERSION** : programming of up to 4 time slots, possibility to deal separately with the ventilation and the element, an electrical temperature sensor, which allows to regulate the energy consumption. Backup fuse holder.

#### + Anti-corrosion treatment

EPOXI painting finish.

### RECOMMENDATIONS

+ 220 V power - IEC plug on top of the unit.

+ Operates on a standard plug / Plan to put a plug above the device.

+ Energy consumption : 530 W/H.

### OPTIONS

+ Available in a free-standing version

+ Disinfection

REF.	↑	↔	↗	Pairs of shoes
K-STOKDRY-A02 (+)	1430			2
K-STOKDRY-A03 (+)	2080	170		3
K-STOKDRY-A04 (+)	1430		330	4
K-STOKDRY-A05 (+)	1750	270		5
K-STOKDRY-A06 (+)	2080			6

**Energy consumption 550 W**

All dimensions are in mm.  
To have the dimensions with the equipment, add:  
90 mm in height  
30 mm in width  
120 mm in depth




Shown model  
K-STOKDRY-A06+  
with gloves bracket



Tube with clap



Ventilation unit



Gloves bracket

### ACCESSORIES

- + Gloves bracket : 2 pairs of gloves for 1 pair of shoes.
- + Helmet bracket : 2 helmets for 1 pair of shoes.



## K-STOKDRY-A

Wall-mounted boot dryer




### WELL THOUGHT-OUT DESIGN FOR AN EASIER USE AND MAINTENANCE

- + Unit on top of the device to secure the electrical system (dust et moisture) and optimize the drying space (an extra pair of shoes).
- + The unit works separately from the rest of the body.
- + Integrated wall-mounting system.
- + **Modularity** : possibility to change the tubes with clap by gloves/ helmet brackets.

*Delivered in a kit (3 boxes) - Simple assembly - Screws supplied.*

### FEATURES OF THE UNIT

- + Powerfull turbine (280 m<sup>3</sup>/h).
- + Heat adjustment of 250, 500 or 1000 W (factory setting of 500 W).
- + Accessible fuse holder (with backup fuse holder).
- + Electrical sensor to regulate the heating temperature.




Shown model  
K-STOKDRY-A06+  
with gloves bracket



### TWO VERSIONS TO CONTROL THE DEVICE


#### STANDARD VERSION :

- + Timer function : 2h, 3h or unlimited hours with an automatic shut-off.
- + Factory setting of 2h can be changed.



#### + VERSION :

- + Integrated programming clock.
- + Up to 4 time slots per day.
- + For each time slot, you can schedule a duration and the type of drying (ventilation with or without heating).



*Instructions for use and settings are supplied.*

