



K-STOCKDRY-A

WALL-MOUNTED BOOT-DRYER

The REFERENCE in wall-mounted boot drying.

The K-STOKDRY-A condenses a maximum of technologie in a minimum of space :

Timer, electronic controls, a fully modular system (boots, gloves, helmets), space-saving design and outstanding ruggedness.

Wide range of sizes and finishes.

Main features::

Optimized Space

The different models offer the possibility to choose the most adapted one to your area, in a reduced space.

Anti-corrosion Treatment

EPOXI painting finish.

Body RAL 7004 - Ventilation unit RAL 7024.

OPTIONS



K-GLOVE-2 For 1 pair of gloves or 1 helmet. To be screwed in place of a shoe support.





K-GLOVE-1 For 1 glove. Tongue to screw onto the back of a shoe support

Heated Air Ventilation System

Small Space Requirement

quickly dry elements (shoes, gloves, helmets...).

The heated air ventilation system, via the tubes with clap, allows to

The K-STOCKDRY-A has a slim design (4 cm), which means

optimises th use of space on the premises. The ventilation unit is

located on the top of K-STOCKDRY-A for an extra pair of shoes.

KORALP SP/

SPACE

SMART STORAGE AND DRYING SOLUTIONS

TIMER VERSION:

Timer function: 2h, 3h or unlimited hours with an automatic shut-off.

Factory setting of 2 hours can be changed.

PROGRAMMABLE VERSION:

Integrated programming clock.

Up to 4 time slot per day.

For each time slot, you can schedule a duration and the type of drying (ventilation with or without heating).

WELL THOUGHT-OUT DESIGN FOR AN EASIER USE AND MAINTENANCE

Unit on top of the device to secure the electrical system (dust ans moisture) and optimize the drying space (an extra pair of shoes).

The unit works separately form the rest of the body

Integrated wall-mouting system.

Modularity: possibility to change the tubes with clap by gloves or helmet holder.





Examples of existing configurations





Delivered in a kit (2 boxes) Simply assembly - Screws supplied.

Main references TIMER	‡	\leftrightarrow	2	Capacity
K-SD-04SP-AT-02.00.00	1430	180		2 Pairs
K-SD-06LP-AT-03.00.00	2080			3 Pairs
K-SD-08SP-AT-04.00.00	1430		330	4 Pairs
K-SD-10MP-AT-05.00.00	1750	270		5 Pairs
K-SD-12LP-AT-06.00.00	2080			6 Pairs
Consumption	550 W			

Dimensions without boots in mm. Capacity: BOOTS (in Nb of pairs)

FEATURES OF THE UNIT

Powerfull turbine (280 m³/h).

Heat adjustment of 250, 500 or 1000 W (factory setting 500 W).

Accessible fuse holder (with backup fuse).

Electrical sensor to regulate the heating temperature.

Recommandations

220V power - IEC plug on top of the unit. Available in 110 V power

Oparates on a standard plug / Plan to put a plug above the boot-dryer.

Consumption: 530 W/H.